

- 2. TH1050 CONDITION (38-44 HRC)
- 3. NONE
- 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

_							
	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005	DRAWN	NAME	DATE		SEASTROM MFG	
		CHECKED			SPRING CLIP		
		ENG APPR.					
		MFG APPR.			3FKING CLIF		
- 1	MATERIAL SEE NOTE 1	Q.A.			1		
		COMMENTS:			1		
- 1	heat treat SEE NOTE 2	NOTE 2				DWG. NO.	
ľ	FINISH				A	4508-25-25-3 -	
	SEE NOTE 3					SHEET 1 OF 1	