

1. BERYLLIUM COPPER, ANNEALED

2. HEAT TREAT: 73-79 HR15N

3. CADMIUM PLATE PER AMS QQ-P-416 TYPE II CLASS 2

4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01	DRAWN	NAME	DATE	SEASTROM MFG	
		CHECKED			SPRING CLIP	
		ENG APPR.				
	THREE PLACE DECIMAL ±.005	MFG APPR.				
E	SEE NOTE 1	Q.A.				
		COMMENTS:				
	HEAT TREAT SEE NOTE 2				SI7E I	DWG. NO. REV.
	FINISH				A	4513-23-37-1-C2
	SEE NOTE 3	DRAWING IS NOT TO SCALE				SHEET 1 OF 1