

1. BERYLLIUM COPPER, ANNEALED

2. HEAT TREAT: 73-79 HR15N

3. ZINC PLATE PER ASTM B633, SC1, Type III or V, Clear

4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

5. DIMENSIONS APPLY PRIOR TO PLATING.

## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGUILAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01	DRAWN	NAME	DATE	SEASTROM MFG		
		CHECKED			SDDING CLID		
		ENG APPR.					
	THREE PLACE DECIMAL ±.005	MFG APPR.			SPRING CLIP		
	SEE NOTE 1	Q.A.					
		COMMENTS:			1		
E	SEE NOTE 2					DWG. NO. REV	·.
	FINISH				Α	4513-33-37-1-Z3  -	
	SEE NOTE 3	DRAWING IS NOT TO SCALE				SHEET 1 OF 1	Ī