

1. BERYLLIUM COPPER, ANNEALED

2. HEAT TREAT: 73-79 HR15N

3. CADMIUM PLATE PER AMS QQ-P-416 TYPE II CLASS 2

4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

5. DIMENSIONS APPLY PRIOR TO PLATING.

## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

	DIMENSIONS ARE IN INCHES		NAME	DATE		SEASTROM MFG
	TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01	DRAWN			3LASTROWTMI G	
		CHECKED			SPRING CLIP	
		ENG APPR.				
	THREE PLACE DECIMAL ±.005	MFG APPR.				SEKING CLIF
	MATERIAL CEE NOTE 1	Q.A.				
E	SEE NOTE 1	COMMENTS:				
	HEAT TREAT					
	SEE NOTE 2				A	DWG. NO.
	FINISH					4513-40-37-1-C2  -
	SEE NOTE 3	DRAWING IS NOT TO SCALE				SHEET 1 OF 1