

NOTES

1. TIN-LEAD DIP PER MIL-DTL-14072, M258. MUST CERT SOLDERABILITY TO MIL-STD-202, M208 - REFLOW ALLOWED, IF REQUIRED

2. SCREW SIZE: 1/4

3. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
SEASTROM MANUFACTURING, ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS
PROHIBITED.

| DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005 MATERIAL BRASS, HALF HARD | | NAME | DATE | | SEASTROM MFG | |
|--|-----------|------|------|----------------|--------------|------|
| | DRAWN | | | 3LASTROWT WILD | | |
| | CHECKED | | | | | |
| | ENG APPR. | | | SOLDER LUG | | |
| | MFG APPR. | | | | | |
| | Q.A. | | | | | |
| | COMMENTS: | | | | | |
| FINISH | | | | | | |
| SEE NOTE 1 | | | | | DWG. NO. | REV. |
| DRAWING IS NOT TO SCALE | 1 | | | Α | 5413-34-TL2 | - |
| | | | | | SHEET 1 | ÔF 1 |