



NOTES

1. PASSIVATE PER AMS2700 METHOD 1 TYPE 2 CLASS 1
2. HEAT TREAT: TH1050 CONDITION (38-44 HRC)
3. NUMBER OF WAVES: 3
4. DIMENSIONS APPLY BEFORE PLATING

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL $\pm 1/32$
ANGULAR: MACH $\pm 1/2$ Deg
TWO PLACE DECIMAL $\pm .01$
THREE PLACE DECIMAL $\pm .005$

MATERIAL
17-7PH STAINLESS STEEL

FINISH
SEE NOTE 1

DRAWING IS NOT TO SCALE

	NAME	DATE
DRAWN		
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		
COMMENTS:		

SEASTROM MFG

WAVE SPRING WASHER

SIZE A	DWG. NO. 5806-170-3-P	REV. -
------------------	---------------------------------	------------------

SHEET 1 OF 1