



NOTES

1. PASSIVATE PER AMS2700 METHOD 1 TYPE 2 CLASS 1
2. HEAT TREAT: TH1050 CONDITION (38-44 HRC)
3. NUMBER OF WAVES: 3
4. DIMENSIONS APPLY BEFORE PLATING

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL $\pm 1/32$
ANGULAR: MACH $\pm 1/2$ Deg
TWO PLACE DECIMAL $\pm .01$
THREE PLACE DECIMAL $\pm .005$

MATERIAL
17-7PH STAINLESS STEEL

FINISH
SEE NOTE 1

DRAWING IS NOT TO SCALE

| | NAME | DATE |
|-----------|------|------|
| DRAWN | | |
| CHECKED | | |
| ENG APPR. | | |
| MFG APPR. | | |
| Q.A. | | |
| COMMENTS: | | |

SEASTROM MFG

WAVE SPRING WASHER

| | | |
|------------------|--------------------------------|-----------|
| SIZE A | DWG. NO. 5806-91-3-P | REV. - |
|------------------|--------------------------------|-----------|

SHEET 1 OF 1