

2. HEAT TREAT: QUENCH & TEMPER 82.5-84.5 HR15N

3. DIMENSIONS APPLY BEFORE PLATING

| THE INFORMATION CONTAINED IN THIS |
|------------------------------------|
| DRAWING IS THE SOLE PROPERTY OF |
| SEASTROM MANUFACTURING. ANY |
| REPRODUCTION IN PART OR AS A WHOLE |
| WITHOUT THE WRITTEN PERMISSION OF |
| SEASTROM MANUFACTURING IS |
| PROHIBITED. |

PROPRIETARY AND CONFIDENTIAL

| | DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005 | DRAWN | IVAIVIL | DATE | SEASTROM MFG | |
|-----|---|-----------|---------|------|----------------|------|
| | | CHECKED | | | | |
| | | ENG APPR. | | | BELLEVILLE | |
| | | MFG APPR. | | | SPRING WASHER | |
| ; | SPRING STEEL | Q.A. | | | | |
| | | COMMENTS: | | | | |
| OLE | SEE NOTE 1 | | | | | REV. |
| | DRAWING IS NOT TO SCALE | | | | A 5808-69-32-N | - |
| | | | | | SHEET 1 | OF 1 |