

2. HEAT TREAT: QUENCH & TEMPER 82.5-84.5 HR15N

3. DIMENSIONS APPLY BEFORE PLATING

| PROPRIETARY AND CONFIDENTIAL |
|--|
| THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE |
| DRAWING IS THE SOLE PROPERTY OF |
| SEASTROM MANUFACTURING. ANY |
| REPRODUCTION IN PART OR AS A WHO |
| |

WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

| | DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/32 ANGULAR: MACH ± 1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005 | | NAME | DATE | SEASTROM MFG | | |
|--|---|-----------|------|------|-----------------------------|------|--|
| | | DRAWN | | | SEASIROM MICG | | |
| | | CHECKED | | | BELLEVILLE SPRING WASHER | | |
| | | ENG APPR. | | | | | |
| | | MFG APPR. | | | | | |
| | SPRING STEEL | Q.A. | | | | | |
| | | COMMENTS: | | | | | |
| | FINISH SEE NOTE 1 | | | | | REV. | |
| | DRAWING IS NOT TO SCALE | | | | A 5808-78-12-N | - | |
| | | | | | SHEET 1 O |)F 1 | |