



PUSH-ON NUT IS ACCEPTABLE WHEN STUD IS PUSHED THRU HOLE, BUT NOT ABLE TO BE PULLED OUT BACKWARDS.

# NOTES

1. HEAT TREAT 82.5 - 84.5 HR15N

2. NONE

## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES  
TOLERANCES:  
FRACTIONAL  $\pm 1/32$   
ANGULAR: MACH  $\pm 1/2$  Deg  
TWO PLACE DECIMAL  $\pm .01$   
THREE PLACE DECIMAL  $\pm .005$

MATERIAL  
SPRING STEEL

FINISH  
SEE NOTE 2

DRAWING IS NOT TO SCALE

	NAME	DATE
DRAWN		
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		
COMMENTS:		

SEASTROM MFG

PUSHON NUT

SIZE <b>A</b>	DWG. NO. <b>2713-10</b>	REV. <b>-</b>
------------------	----------------------------	------------------

SHEET 1 OF 1