



## **SIZING**

HOUSING DIA.: Ø.250

GROOVE DIA.: Ø.268

GROOVE WIDTH: Ø.020

- NOTES
  1. PHOSPHATE COATING
- 2. STYLE: INTERNAL
- 3. DIMENSIONS APPLY PRIOR TO PLATING.

	TWO PLA
PROPRIETARY AND CONFIDENTIAL	THREE PLA
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING, ANY	MATERIAL SPRING
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS	SEE NOT

PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005  MATERIAL SPRING STEEL	DRAWN	NAME	DATE	SEASTROM MFG		
	CHECKED					
	ENG APPR.			RETAINING RING		
	MFG APPR.			RETAINING KING		
	Q.A.					
	COMMENTS:					
SEE NOTE 1					REV.	
DRAWING IS NOT TO SCALE				A 2725-1-25	-	
DRAWING IS NOT TO SCALE				SHEET 1 C	)F 1	

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005		NAME	DATE		
	DRAWN			SEASTROM MFG	
	CHECKED			RETAINING RING	
	ENG APPR.				
	MFG APPR.			RETAINING KING	
SPRING STEEL	Q.A.				
	COMMENTS:				
SEE NOTE 1				SIZE DWG. NO. 2725-1-25	RE
DRAWING IS NOT TO SCALE				SHEET 1	OF