



SIZING

HOUSING DIA.: Ø2.688

GROOVE DIA.: Ø2.848

GROOVE WIDTH: Ø.103

- NOTES
 1. PHOSPHATE COATING
- 2. STYLE: INTERNAL
- 3. DIMENSIONS APPLY PRIOR TO PLATING.

	TW
PROPRIETARY AND CONFIDENTIAL	THE
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY	SPR
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF	FINISH

SEASTROM MANUFACTURING IS

PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005 MATERIAL SPRING STEEL	DRAWN	NAME	DATE	SEASTROM MFG	
	CHECKED			RETAINING RING	
	ENG APPR.				
	MFG APPR.			KLIAINING KING	
	Q.A.				
	COMMENTS:				
SEE NOTE 1					EV.
DRAWING IS NOT TO SCALE				A 2725-40-268 -	
DIAWING IS NOT TO SCALE				SHEET 1 OF	- 1

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01		NAME	DATE			
	DRAWN			SEASTROM MFG		
	CHECKED				_	
	ENG APPR.			RETAINING RING		
	THREE PLACE DECIMAL ±.005	MFG APPR.			RETAINING KING	
SPRING STEEL	Q.A.					
	COMMENTS:					
	SEE NOTE 1				SIZE DWG. NO. 2725-40-268	REV
DRAWING IS NOT TO SCALE					SHEET 1 OF	= 1