



## **SIZING**

SHAFT DIA.: Ø2.500

GROOVE DIA.: Ø2.360

GROOVE WIDTH: Ø.086

## **NOTES**

1. PHOSPHATE COATING

2. STYLE: EXTERNAL

3. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005	DRAWN	NAME	DATE	SEASTROM MFG	
		CHECKED				
		ENG APPR.			RETAINING RING	
		MFG APPR.			KLIAIINING KING	
	SPRING STEEL	Q.A.				
		COMMENTS:			7	
	SEE NOTE 1				SIZE DWG, NO.	
	DRAWING IS NOT TO SCALE	<u> </u>			A 2727-39-250 -	
	5.0 S .0.1101 10 00/ KEE	l			SHEET 1 OF 1	

CHES		NAME	DATE				
0.120	DRAWN			SEASTROM MFG			
2 Deg	CHECKED						
±.01	ENG APPR.			RETAINING RING			
L ±.005	MFG APPR.						
	Q.A.						
	COMMENTS:						
				SIZE DWG. NO.	REV.		
OSCALE				A 2727-39-250	-		