



NOTES

- 1. SPRING STEEL, ANNEALED
- 2. QUENCH & TEMPER 80-83 HR15N
- 3. NONE
- 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005	DRAWN	NAME	DATE	SEASTROM MFG		
		CHECKED					
		ENG APPR.			SPRING CLIP		
		MFG APPR.			SEKTING CLIF		
	MATERIAL	Q.A.					
	SEE NOTE 1	COMMENTS:			1		
Ξ	HEAT TREAT				0175	I	
	SEE NOTE 2				217F	DWG. NO. 4504-33-25-2	REV.
	FINISH				_		
	SEE NOTE 3	DRAWING IS NOT TO SCALE				SHEET 1 O	F 1