



NOTES

- 1. SPRING STEEL, ANNEALED
- 2. QUENCH & TEMPER 80-83 HR15N
- 3. TIN PER ASTM B545 CLASS B w/BAKE
- 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
- 5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005	DRAWN	NAME	DATE	SEASTROM MFG		
		CHECKED					
		ENG APPR.			SPRING CLIP		
		MFG APPR.					
	MATERIAL CEE NOTE 1	Q.A.					
E	SEE NOTE 1	COMMENTS:					
	HEAT TREAT						
	SEE NOTE 2	= 2				^{DWG. NO.} 4505-18X35-37-2-T	REV.
	SEE NOTE 3				А	4303-10/33-37-2-1	-
		DRAWING IS NOT TO SCALE			SHEET 1 OF		F 1