



NOTES
1. BERYLLIUM COPPER, ANNEALED

2. HEAT TREAT: 73-79 HR15N

3. NICKEL PLATE PER AMS QQ-N-290 CLASS 1 GRADE G

4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ±1/32 ANGULAR: MACH ±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005		NAME	DATE	SEASTROM MFG		
	DRAWN					
	CHECKED			SPRING CLIP		
	ENG APPR.					
	MFG APPR.					
MATERIAL SEE NOTE 1	Q.A.			SIZE A	DWG. NO. 4511-37-75-1-N	REV. -
HEAT TREAT SEE NOTE 2	COMMENTS:					
FINISH SEE NOTE 3	DRAWING IS NOT TO SCALE			SHEET 1 OF 1		