



- NOTES
- 1. BERYLLIUM COPPER, ANNEALED
 - 2. HEAT TREAT: 73-79 HR15N
 - 3. TIN PER ASTM B545 CLASS B
 - 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
 - 5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

| | | | | | | |
|---|-------------------------|------|------|------------------|-----------------------------------|------------------|
| DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ±1/32 ANGULAR: MACH ±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005 | | NAME | DATE | SEASTROM MFG | | |
| | DRAWN | | | | | |
| | CHECKED | | | SPRING CLIP | | |
| | ENG APPR. | | | | | |
| | MFG APPR. | | | | | |
| MATERIAL SEE NOTE 1 | Q.A. | | | SIZE A | DWG. NO. 4511-37-75-1-T | REV. - |
| HEAT TREAT SEE NOTE 2 | COMMENTS: | | | | | |
| FINISH SEE NOTE 3 | DRAWING IS NOT TO SCALE | | | SHEET 1 OF 1 | | |