



NOTES  
1. SPRING STEEL, ANNEALED

2. QUENCH & TEMPER: 80-83 HR15N

3. CADMIUM PLATE PER AMS QQ-P-416 TYPE II CLASS 2 w/BAKE

4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

5. DIMENSIONS APPLY PRIOR TO PLATING.

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/32 ANGULAR: MACH ± 1/2 Deg TWO PLACE DECIMAL    ±.01 THREE PLACE DECIMAL   ±.005		NAME	DATE	SEASTROM MFG   SPRING CLIP		
	DRAWN					
	CHECKED					
	ENG APPR.					
	MFG APPR.					
MATERIAL SEE NOTE 1	COMMENTS:			SIZE <b>A</b>	DWG. NO.  4511-40-50-2-C2	REV. -
HEAT TREAT SEE NOTE 2						
FINISH SEE NOTE 3						
DRAWING IS NOT TO SCALE				SHEET 1 OF 1		