



- NOTES
- 1. BERYLLIUM COPPER, ANNEALED
 - 2. HEAT TREAT: 73-79 HR15N

- 3. NICKEL PLATE PER AMS QQ-N-290 CLASS 1 GRADE G
- 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
- 5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ±1/32 ANGULAR: MACH ±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005		NAME	DATE	SEASTROM MFG		
	DRAWN					
	CHECKED			SPRING CLIP		
	ENG APPR.					
	MFG APPR.					
MATERIAL SEE NOTE 1	Q.A.			COMMENTS:		
HEAT TREAT SEE NOTE 2						
FINISH SEE NOTE 3	DRAWING IS NOT TO SCALE			SIZE A	DWG. NO. 4511-43-37-1-N	REV. -
				SHEET 1 OF 1		