



- NOTES
- 1. BERYLLIUM COPPER, ANNEALED
 - 2. HEAT TREAT: 73-79 HR15N
 - 3. TIN PER ASTM B545 CLASS B
 - 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
 - 5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

| | | | | | |
|--|--------------------------|----------------------|-----------|-----------------------------------|------------------|
| DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL $\pm 1/32$ ANGULAR: MACH $\pm 1/2$ Deg TWO PLACE DECIMAL $\pm .01$ THREE PLACE DECIMAL $\pm .005$ | | NAME | DATE | SEASTROM MFG | |
| | | DRAWN | | | |
| | | CHECKED | | SPRING CLIP | |
| | | ENG APPR. | | | |
| | | MFG APPR. | | | |
| MATERIAL SEE NOTE 1 | HEAT TREAT SEE NOTE 2 | FINISH SEE NOTE 3 | COMMENTS: | | SIZE A |
| DRAWING IS NOT TO SCALE | | | | DWG. NO. 4511-43-37-1-T | REV. - |
| | | | | | SHEET 1 OF 1 |