



- NOTES
- 1. BERYLLIUM COPPER, ANNEALED
  - 2. HEAT TREAT: 73-79 HR15N
  - 3. TIN PER ASTM B545 CLASS B
  - 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
  - 5. DIMENSIONS APPLY PRIOR TO PLATING.

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL $\pm 1/32$ ANGULAR: MACH $\pm 1/2$ Deg TWO PLACE DECIMAL $\pm .01$ THREE PLACE DECIMAL $\pm .005$		NAME	DATE	SEASTROM MFG	
		DRAWN			
		CHECKED		SPRING CLIP	
		ENG APPR.			
		MFG APPR.			
MATERIAL SEE NOTE 1	Q.A.			COMMENTS:	
HEAT TREAT SEE NOTE 2					
FINISH SEE NOTE 3					
		DRAWING IS NOT TO SCALE		SIZE <b>A</b>	DWG. NO. 4511-43-75-1-T
				REV. -	SHEET 1 OF 1