



**No. HOLES: 1**

NOTES  
1. BERYLLIUM COPPER, ANNEALED

2. HEAT TREAT: 73-79 HR15N

3. SILVER PLATE PER ASTM B700 TYPE 1 GRADE A CLASS S, 2.5μm TH  
w/NICKEL UNDERPLATE

4. DIMENSIONS ARE TAKEN WITH THE PART  
CLAMPED TO A FLAT SURFACE AND A DUMMY  
COMPONENT IN PLACE.

5. DIMENSIONS APPLY PRIOR TO PLATING.

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS  
DRAWING IS THE SOLE PROPERTY OF  
SEASTROM MANUFACTURING. ANY  
REPRODUCTION IN PART OR AS A WHOLE  
WITHOUT THE WRITTEN PERMISSION OF  
SEASTROM MANUFACTURING IS  
PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL $\pm 1/32$ ANGULAR: MACH $\pm 1/2$ Deg TWO PLACE DECIMAL $\pm .01$ THREE PLACE DECIMAL $\pm .005$		NAME	DATE	SEASTROM MFG	
		DRAWN			
		CHECKED		SPRING CLIP	
		ENG APPR.			
		MFG APPR.			
MATERIAL SEE NOTE 1	Q.A.			DRAWING IS NOT TO SCALE	
HEAT TREAT SEE NOTE 2	COMMENTS:				
FINISH SEE NOTE 3	SIZE A	DWG. NO.	4511-50-37-1-S	REV. -	SHEET 1 OF 1