



NOTES

- 1. BERYLLIUM COPPER, ANNEALED
- 2. HEAT TREAT: 73-79 HR15N
- 3. CADMIUM PLATE PER AMS QQ-P-416 TYPE II CLASS 2
- 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
- 5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL $\pm 1/32$ ANGULAR: MACH $\pm 1/2$ Deg TWO PLACE DECIMAL $\pm .01$ THREE PLACE DECIMAL $\pm .005$		NAME	DATE	SEASTROM MFG	
		DRAWN			
		CHECKED		SPRING CLIP	
		ENG APPR.			
		MFG APPR.			
MATERIAL SEE NOTE 1	HEAT TREAT SEE NOTE 2	FINISH SEE NOTE 3	COMMENTS:		SIZE A
DRAWING IS NOT TO SCALE				DWG. NO. 4511-56-37-1-C2	REV. -
				SHEET 1 OF 1	