



- NOTES
- 1. BERYLLIUM COPPER, ANNEALED
  - 2. HEAT TREAT: 73-79 HR15N
  - 3. TIN PER ASTM B545 CLASS B
  - 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
  - 5. DIMENSIONS APPLY PRIOR TO PLATING.

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

|   |                         |      |      |                  |                            |           |
|---|-------------------------|------|------|------------------|----------------------------|-----------|
| DIMENSIONS ARE IN INCHES<br>TOLERANCES:<br>FRACTIONAL ±1/32<br>ANGULAR: MACH ±1/2 Deg<br>TWO PLACE DECIMAL    ±.01<br>THREE PLACE DECIMAL   ±.005 |                         | NAME | DATE | SEASTROM MFG     |                            |           |
|   | DRAWN                   |      |      |                  |                            |           |
|   | CHECKED                 |      |      | SPRING CLIP      |                            |           |
|   | ENG APPR.               |      |      |                  |                            |           |
|   | MFG APPR.               |      |      |                  |                            |           |
| MATERIAL<br>SEE NOTE 1  | Q.A.                    |      |      | COMMENTS:        |                            |           |
| HEAT TREAT<br>SEE NOTE 2  |                         |      |      |                  |                            |           |
| FINISH<br>SEE NOTE 3  | DRAWING IS NOT TO SCALE |      |      | SIZE<br><b>A</b> | DWG. NO.<br>4511-56-50-1-T | REV.<br>- |
|   |                         |      |      | SHEET 1 OF 1     |                            |           |