



- NOTES
1. SPRING STEEL, ANNEALED
  2. QUENCH & TEMPER 80-83 HR15N
  3. NONE

4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/32 ANGULAR: MACH ± 1/2 Deg TWO PLACE DECIMAL ± .01 THREE PLACE DECIMAL ± .005		NAME	DATE	<b>SEASTROM MFG</b>	
MATERIAL SEE NOTE 1	DRAWN				
HEAT TREAT SEE NOTE 2	CHECKED			SIZE	DWG. NO.
FINISH SEE NOTE 3	ENG APPR.			<b>A</b>	<b>4527-17-25-2</b>
	MFG APPR.				REV.
	Q.A.				-
	COMMENTS:				SHEET 1 OF 1
	DRAWING IS NOT TO SCALE				