



NOTES  
1. BERYLLIUM COPPER, ANNEALED

2. HEAT TREAT: 73-79 HR15N

3. NONE

4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

|  |                         |      |                  |                          |
|--|-------------------------|------|------------------|--------------------------|
| DIMENSIONS ARE IN INCHES<br>TOLERANCES:<br>FRACTIONAL ± 1/32<br>ANGULAR: MACH ± 1/2 Deg<br>TWO PLACE DECIMAL ± .01<br>THREE PLACE DECIMAL ± .005 | NAME                    | DATE | SEASTROM MFG     |                          |
|  | DRAWN                   |      |                  |                          |
|  | CHECKED                 |      | SPRING CLIP      |                          |
|  | ENG APPR.               |      |                  |                          |
|  | MFG APPR.               |      | Q.A.             |                          |
| MATERIAL<br>SEE NOTE 1   | COMMENTS:               |      | SIZE<br><b>A</b> | DWG. NO.<br>4527-17-62-1 |
| HEAT TREAT<br>SEE NOTE 2   |                         |      |                  | REV.<br>-                |
| FINISH<br>SEE NOTE 3   | DRAWING IS NOT TO SCALE |      | SHEET 1 OF 1     |                          |