



No. HOLES: 3

- NOTES
1. BERYLLIUM COPPER, ANNEALED
 2. HEAT TREAT: 73-79 HR15N
 3. TIN PER ASTM B545 CLASS B
 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
 5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/32 ANGULAR: MACH ± 1/2 Deg TWO PLACE DECIMAL ± .01 THREE PLACE DECIMAL ± .005	NAME	DATE	SEASTROM MFG	
	DRAWN			
	CHECKED		SPRING CLIP	
	ENG APPR.			
	MFG APPR.			
MATERIAL	COMMENTS:		SIZE	REV.
SEE NOTE 1			A	-
HEAT TREAT			DWG. NO. 4527-19-112-1-T	
SEE NOTE 2			SHEET 1 OF 1	
FINISH	DRAWING IS NOT TO SCALE			
SEE NOTE 3				