



NOTES  
1. SPRING STEEL, ANNEALED

2. QUENCH & TEMPER 80-83 HR15N

3. NONE

4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

**No. HOLES: 2**

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/32 ANGULAR: MACH ± 1/2 Deg TWO PLACE DECIMAL ± .01 THREE PLACE DECIMAL ± .005		NAME	DATE	SEASTROM MFG	
MATERIAL SEE NOTE 1	HEAT TREAT SEE NOTE 2	DRAWN			
FINISH SEE NOTE 3		CHECKED		SIZE <b>A</b>	DWG. NO. 4527-19-37-2
		ENG APPR.		REV. -	
		MFG APPR.		SHEET 1 OF 1	
		Q.A.		DRAWING IS NOT TO SCALE	
		COMMENTS:			