



- NOTES
1. SPRING STEEL, ANNEALED
  2. QUENCH & TEMPER 80-83 HR15N
  3. NONE

4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

**PROPRIETARY AND CONFIDENTIAL**  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/32 ANGULAR: MACH ± 1/2 Deg TWO PLACE DECIMAL ± .01 THREE PLACE DECIMAL ± .005		NAME	DATE	<b>SEASTROM MFG</b>
MATERIAL SEE NOTE 1	HEAT TREAT SEE NOTE 2	DRAWN	CHECKED	
FINISH SEE NOTE 3	COMMENTS:	ENG APPR.	MFG APPR.	SIZE <b>A</b> DWG. NO. <b>4527-19-62-2</b>
DRAWING IS NOT TO SCALE			Q.A.	REV. -
				SHEET 1 OF 1