



### No. HOLES: 1

#### NOTES

1. BERYLLIUM COPPER, ANNEALED

2. HEAT TREAT: 73-79 HR15N

3. TIN PER ASTM B545 CLASS B

4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

5. DIMENSIONS APPLY PRIOR TO PLATING.

#### PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES  
TOLERANCES:  
FRACTIONAL  $\pm 1/32$   
ANGULAR: MACH  $\pm 1/2$  Deg  
TWO PLACE DECIMAL  $\pm .01$   
THREE PLACE DECIMAL  $\pm .005$

MATERIAL  
SEE NOTE 1

HEAT TREAT  
SEE NOTE 2

FINISH  
SEE NOTE 3

| NAME                    | DATE |
|-------------------------|------|
| DRAWN                   |      |
| CHECKED                 |      |
| ENG APPR.               |      |
| MFG APPR.               |      |
| Q.A.                    |      |
| COMMENTS:               |      |
| DRAWING IS NOT TO SCALE |      |

SEASTROM MFG

SPRING CLIP

| SIZE | DWG. NO.       | REV. |
|------|----------------|------|
| A    | 4547-43-43-1-T | -    |

SHEET 1 OF 1