



### **No. HOLES: 1**

#### NOTES

1. SPRING STEEL, ANNEALED
2. QUENCH & TEMPER: 80-83 HR15N
3. CADMIUM PLATE PER AMS QQ-P-416 TYPE II CLASS 2 w/BAKE
4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
5. DIMENSIONS APPLY PRIOR TO PLATING.

#### **PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES  
TOLERANCES:  
FRACTIONAL  $\pm 1/32$   
ANGULAR: MACH  $\pm 1/2$  Deg  
TWO PLACE DECIMAL  $\pm .01$   
THREE PLACE DECIMAL  $\pm .005$

MATERIAL  
SEE NOTE 1

HEAT TREAT  
SEE NOTE 2

FINISH  
SEE NOTE 3

| NAME                    | DATE |
|-------------------------|------|
| DRAWN                   |      |
| CHECKED                 |      |
| ENG APPR.               |      |
| MFG APPR.               |      |
| Q.A.                    |      |
| COMMENTS:               |      |
| DRAWING IS NOT TO SCALE |      |

**SEASTROM MFG**

**SPRING CLIP**

| SIZE     | DWG. NO.               | REV.     |
|----------|------------------------|----------|
| <b>A</b> | <b>4547-50-43-2-C2</b> | <b>-</b> |

SHEET 1 OF 1