



No. HOLES: 1

NOTES

1. SPRING STEEL, ANNEALED
2. QUENCH & TEMPER 80-83 HR15N
3. TIN PER ASTM B545 CLASS B w/BAKE
4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/32 ANGULAR: MACH ± 1/2 Deg TWO PLACE DECIMAL ± .01 THREE PLACE DECIMAL ± .005		NAME	DATE	SEASTROM MFG	
MATERIAL SEE NOTE 1	DRAWN				
HEAT TREAT SEE NOTE 2	CHECKED			SPRING CLIP	
FINISH SEE NOTE 3	ENG APPR.				
	MFG APPR.			SIZE A DWG. NO. 4549-40-50-2-T REV. -	
	Q.A.				
COMMENTS: DRAWING IS NOT TO SCALE				SHEET 1 OF 1	