



- NOTES
- 1. SPRING STEEL, ANNEALED
  - 2. QUENCH & TEMPER: 80-83 HR15N
  - 3. NONE

4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL $\pm 1/32$ ANGULAR: MACH $\pm 1/2$ Deg TWO PLACE DECIMAL $\pm .01$ THREE PLACE DECIMAL $\pm .005$		NAME	DATE	<b>SEASTROM MFG</b>  <b>SPRING CLIP</b>	
MATERIAL SEE NOTE 1		DRAWN			
HEAT TREAT SEE NOTE 2		CHECKED			
FINISH SEE NOTE 3		ENG APPR.			
		MFG APPR.			
		Q.A.		SIZE <b>A</b> DWG. NO. <b>4549-40-50-2</b> REV. <b>-</b>	
		COMMENTS:			
DRAWING IS NOT TO SCALE				SHEET 1 OF 1	