



No. HOLES: 2

- NOTES
- 1. BERYLLIUM COPPER, ANNEALED
 - 2. HEAT TREAT: 73-79 HR15N

- 3. SILVER PLATE PER ASTM B700 TYPE 1 GRADE A CLASS S, 2.5μm TH w/NICKEL UNDERPLATE
- 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
- 5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL $\pm 1/32$ ANGULAR: MACH $\pm 1/2$ Deg TWO PLACE DECIMAL $\pm .01$ THREE PLACE DECIMAL $\pm .005$		NAME	DATE	SEASTROM MFG SPRING CLIP	
MATERIAL SEE NOTE 1		DRAWN			
HEAT TREAT SEE NOTE 2		CHECKED			
FINISH SEE NOTE 3		ENG APPR.			
		MFG APPR.			
		Q.A.		DRAWING IS NOT TO SCALE	
		COMMENTS:			
SIZE A	DWG. NO. 4549-50-50-1-S	REV. -	SHEET 1 OF 1		