



- NOTES
- 1. BERYLLIUM COPPER, ANNEALED
  - 2. HEAT TREAT: 73-79 HR15N
  - 3. TIN PER ASTM B545 CLASS B
  - 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
  - 5. DIMENSIONS APPLY PRIOR TO PLATING.

**PROPRIETARY AND CONFIDENTIAL**

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ±1/32 ANGULAR: MACH ±1/2 Deg TWO PLACE DECIMAL    ±.01 THREE PLACE DECIMAL   ±.005		NAME	DATE	SEASTROM MFG		
	DRAWN					
	CHECKED			SPRING CLIP		
	ENG APPR.					
	MFG APPR.					
MATERIAL SEE NOTE 1	Q.A.			COMMENTS:		
HEAT TREAT SEE NOTE 2						
FINISH SEE NOTE 3	DRAWING IS NOT TO SCALE			SIZE <b>A</b>	DWG. NO. <b>4549-50-50-1-T</b>	REV. <b>-</b>
				SHEET 1 OF 1		