



- NOTES
1. BERYLLIUM COPPER, ANNEALED
 2. HEAT TREAT: 73-79 HR15N
 3. TIN PER ASTM B545 CLASS B
 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
 5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/32 ANGULAR: MACH ± 1/2 Deg TWO PLACE DECIMAL ± .01 THREE PLACE DECIMAL ± .005	
MATERIAL SEE NOTE 1	
HEAT TREAT SEE NOTE 2	
FINISH SEE NOTE 3	

	NAME	DATE
DRAWN		
CHECKED		
ENG APPR.		
MFG APPR.		
Q.A.		
COMMENTS:		
DRAWING IS NOT TO SCALE		

SEASTROM MFG		
SPRING CLIP		
SIZE A	DWG. NO. 4549-50-75-1-T	REV. -
		SHEET 1 OF 1