



- NOTES
- 1. BERYLLIUM COPPER, ANNEALED
 - 2. HEAT TREAT: 73-79 HR15N
 - 3. CADMIUM PLATE PER AMS QQ-P-416 TYPE II CLASS 2
 - 4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.
 - 5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL $\pm 1/32$ ANGULAR: MACH $\pm 1/2$ Deg TWO PLACE DECIMAL $\pm .01$ THREE PLACE DECIMAL $\pm .005$		NAME	DATE	SEASTROM MFG	
		DRAWN			
		CHECKED		SPRING CLIP	
		ENG APPR.			
		MFG APPR.			
MATERIAL SEE NOTE 1	Q.A.			DRAWING IS NOT TO SCALE	
HEAT TREAT SEE NOTE 2	COMMENTS:				
FINISH SEE NOTE 3	SIZE A	DWG. NO.	4550-37-75-1-C2	REV. -	SHEET 1 OF 1