



- NOTES
- 1. SPRING STEEL, ANNEALED
 - 2. QUENCH & TEMPER: 80-83 HR15N
 - 3. NONE

4. DIMENSIONS ARE TAKEN WITH THE PART CLAMPED TO A FLAT SURFACE AND A DUMMY COMPONENT IN PLACE.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL $\pm 1/32$ ANGULAR: MACH $\pm 1/2$ Deg TWO PLACE DECIMAL $\pm .01$ THREE PLACE DECIMAL $\pm .005$		NAME	DATE	SEASTROM MFG	
MATERIAL SEE NOTE 1		DRAWN			
HEAT TREAT SEE NOTE 2		CHECKED		SPRING CLIP	
FINISH SEE NOTE 3		ENG APPR.			
DRAWING IS NOT TO SCALE		MFG APPR.		SIZE A DWG. NO. 4551-37-75-2 REV. -	
		Q.A.			
		COMMENTS:		SHEET 1 OF 1	