



NOTES

1. SPRING STEEL, ANNEALED

2. QUENCH & TEMPER: 80-83 HR15N

3. SILVER PLATE PER ASTM B700 TYPE 1 GRADE A CLASS S, 2.5µm TH
w/NICKEL UNDERPLATE w/BAKE

4. DIMENSIONS ARE TAKEN WITH THE PART
CLAMPED TO A FLAT SURFACE AND A DUMMY
COMPONENT IN PLACE.

5. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
SEASTROM MANUFACTURING. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS
PROHIBITED.

| | | | | | |
|--|-------------------------|------|--------------|----------------|------|
| DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/32 ANGULAR: MACH ± 1/2 Deg TWO PLACE DECIMAL ± .01 THREE PLACE DECIMAL ± .005 | NAME | DATE | SEASTROM MFG | | |
| | DRAWN | | | | |
| | CHECKED | | SPRING CLIP | | |
| | ENG APPR. | | | | |
| | MFG APPR. | | | | |
| Q.A. | | | SIZE | DWG. NO. | REV. |
| COMMENTS: | | | A | 4567-37-75-2-S | - |
| MATERIAL SEE NOTE 1 | DRAWING IS NOT TO SCALE | | SHEET 1 OF 1 | | |
| HEAT TREAT SEE NOTE 2 | | | | | |
| FINISH SEE NOTE 3 | | | | | |