


NOMINAL BRAID WIDTH	NOMINAL BRAID THICKNESS	NOMINAL CIRC MILS	CAPACITY AMPS	APPROX AWG EQUIV
.500	.030	9,600	53	10



MATERIALS
GROUND ENDS: COPPER (TIN SOLDER DIP)
BRAID: TINNED COPPER
INSULATION: NONE

ASSEMBLY
TERMINALS (GROUND ENDS) ARE
CRIMPED AND SOFT TIN SOLDERED TO
BRAID.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
SEASTROM MANUFACTURING. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS
PROHIBITED.

DIMENSIONS ARE IN INCHES ALL DIMENSIONS ARE FOR REFERENCE ONLY		NAME	DATE	SEASTROM MFG					
	DRAWN								
	CHECKED			GROUND STRAP					
	ENG APPR.								
	MFG APPR.								
Q.A.									
MATERIAL SEE NOTES	COMMENTS:					SIZE A		DWG. NO. 5025-4-16.500	
FINISH SEE NOTES									
DRAWING IS NOT TO SCALE				SHEET 1 OF 1					