

NOTES 1. TIN-LEAD DIP PER MIL-DTL-14072, M258. MUST CERT SOLDERABILITY TO MIL-STD-202, M208 - REFLOW ALLOWED, IF REQUIRED

2. SCREW SIZE: 2

3. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
SEASTROM MANUFACTURING. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS
PROHIBITED.

	DIMENSIONS ARE IN INCHES		NAME	DATE		SEASTROM MFG	
	TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005	DRAWN			3LASTROWING		
		CHECKED					
		ENG APPR.			SOLDER LUG		
		MFG APPR.					
	BRASS, HALF HARD	Q.A.					
		COMMENTS:			1		
	FINISH						
	SEE NOTE 1					DWG. NO.	REV.
	DRAWING IS NOT TO SCALE				Α	5413-102-TL2	-
						SHEET 1 (	OF 1