

NOTES 1. TIN-LEAD DIP PER MIL-DTL-14072, M258. MUST CERT SOLDERABILITY TO MIL-STD-202, M208 - REFLOW ALLOWED, IF REQUIRED

2. SCREW SIZE: 4

3. DIMENSIONS APPLY PRIOR TO PLATING.

I KOI KILIAKI AND CONTIDENTIAL					
THE INFORMATION CONTAINED IN THIS					
DRAWING IS THE SOLE PROPERTY OF					
SEASTROM MANUFACTURING. ANY					
REPRODUCTION IN PART OR AS A WHOLE					
WITHOUT THE WRITTEN PERMISSION OF					
SEASTROM MANUFACTURING IS PROHIBITED.					

TOLERANCES: FRACTIONAL±1, ANGULAR: MAC	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg		NAME	DATE	SEASTROM MFG
		DRAWN			3LASIKOM MI G
		CHECKED			SOLDER LUG
	TWO PLACE DECIMAL ±.01	ENG APPR.			
	THREE PLACE DECIMAL ±.005	MFG APPR.			
İ	BRASS, HALF HARD	Q.A.			
		COMMENTS:			1
	SEE NOTE 1				SIZE DWG. NO.
İ	DRAWING IS NOT TO SCALE				A 5413-104-TL2
	DRAWING IS NOT TO SCALE				SHEET 1 OF 1