

NOTES 1. TIN-LEAD DIP PER MIL-DTL-14072, M258. MUST CERT SOLDERABILITY TO MIL-STD-202, M208 - REFLOW ALLOWED, IF REQUIRED

2. SCREW SIZE: 6

3. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005		NAME	DATE	SEASTROM MFG
		DRAWN			3LASTROM MIG
		CHECKED			SOLDER LUG
		ENG APPR.			
		MFG APPR.			
İ	BRASS, HALF HARD	Q.A.			1
		COMMENTS:			1
	SEE NOTE 1				SIZE DWG. NO.
	DRAWING IS NOT TO SCALE				A 5413-106-TL2
	DRAWING IS NOT TO SCALE				SHEET 1 OF 1