

NOTES
1. TIN-LEAD PER AMS-P-81728 w/COPPER UNDERPLATE. MUST CERT SOLDERABILITY TO MIL-STD-202, M208

2. SCREW SIZE: 1/2

3. DIMENSIONS APPLY PRIOR TO PLATING.

I KOI KILIAKI AND CONIDE	ITIIAL
THE INFORMATION CONTAIN	IED IN THIS
DRAWING IS THE SOLE PROP	ERTY OF
SEASTROM MANUFACTURING	G. ANY
REPRODUCTION IN PART OR	AS A WHOLE
WITHOUT THE WRITTEN PERM	ISSION OF
SEASTROM MANUFACTURING	G IS
PROHIBITED.	

	DIMENSIONS ARE IN INCHES		NAME	DATE	SEASTROM MFG
	TOLERANCES:	DRAWN			3LASTROM MI G
FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01	CHECKED				
	ENG APPR.			SOLDER LUG	
	THREE PLACE DECIMAL ±.005	MFG APPR.			30LDLK LUG
	BDVCC HVIEHVDD	Q.A.			
		COMMENTS:			
	SEE NOTE 1				SIZE DWG. NO.
Ī	DRAWING IS NOT TO SCALE				A 5413-124-TL1
					I SHEET 1 OF 1