

NOTES 1. TIN-LEAD DIP PER MIL-DTL-14072, M258. MUST CERT SOLDERABILITY TO MIL-STD-202, M208 - REFLOW ALLOWED, IF REQUIRED

2. SCREW SIZE: 8

3. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
SEASTROM MANUFACTURING. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS
PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005		NAME	DATE	SEASTROM MFG		
		DRAWN			SEASIKOM MICG		
		CHECKED					
		ENG APPR.			SOLDER LUG		
		MFG APPR.					
	MATERIAL BRASS, HALF HARD	Q.A.					
		COMMENTS:			7		
	SEE NOTE 1				SIZE DWG. NO.	<i>/</i> .	
	DRAWING IS NOT TO SCALE				A 5413-30-TL2 -		
	DIVAMING IS NOT TO SCALE				I SHEET 1 OF 1	1	