

NOTES
1. TIN-LEAD PER AMS-P-81728 w/COPPER UNDERPLATE. MUST CERT SOLDERABILITY TO MIL-STD-202, M208

2. SCREW SIZE: 6

3. DIMENSIONS APPLY PRIOR TO PLATING.

| PROPRIETARY AND CONFIDENTIAL       |
|------------------------------------|
| THE INFORMATION CONTAINED IN THIS  |
| DRAWING IS THE SOLE PROPERTY OF    |
| SEASTROM MANUFACTURING. ANY        |
| REPRODUCTION IN PART OR AS A WHOLE |
| WITHOUT THE WRITTEN PERMISSION OF  |
| SEASTROM MANUFACTURING IS          |
| PROHIBITED.                        |
|                                    |

|  | DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 |              | NAME | DATE | SEASTROM MFG   |    |
|--|---|--------------|------|------|----------------|----|
|  |   | DRAWN        |      |      | 3LASTROM MI G  |    |
|  |   | CHECKED      |      |      |                |    |
|  |   | ENG APPR.    |      |      | SOLDER LUG     |    |
|  | THREE PLACE DECIMAL ±.005   | MFG APPR.    |      |      |                |    |
|  | BRASS, HALF HARD  | Q.A.         |      |      |                |    |
|  |   | COMMENTS:    |      |      |                |    |
|  | SEE NOTE 1  |              |      |      | SIZE DWG. NO.  | ٧. |
|  | DRAWING IS NOT TO SCALE   | A 5413-/-IL1 |      |      | THE OTIO / ILI |    |
|  |   |              |      |      | I SHEET 1 OF 1 | 1  |