

NOTES
1. TIN-LEAD PER AMS-P-81728 w/COPPER UNDERPLATE. MUST CERT SOLDERABILITY TO MIL-STD-202, M208

2. SCREW SIZE: 10

3. DIMENSIONS APPLY PRIOR TO PLATING.

F	ROPRIETARY AND CONFIDENTIAL
T	THE INFORMATION CONTAINED IN THIS
[DRAWING IS THE SOLE PROPERTY OF
S	SEASTROM MANUFACTURING. ANY
F	REPRODUCTION IN PART OR AS A WHOLE
١	WITHOUT THE WRITTEN PERMISSION OF
S	SEASTROM MANUFACTURING IS
F	PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01	DRAWN	NAME	DATE	SEASTROM MFG		
		CHECKED					
		ENG APPR.				SOLDER LUG	
	THREE PLACE DECIMAL ±.005	MFG APPR.				30LDER LUG	
	MATERIAL	Q.A.					
	BRASS, HALF HARD	COMMENTS:					
Ξ	FINISH				SIZE	DWG. NO.	RFV.
	SEE NOTE 1				A	5413-84-TL1	-
	DRAWING IS NOT TO SCALE					SHEET 1	OF 1