

NOTES

1. TIN-LEAD DIP PER MIL-DTL-14072, M258. MUST CERT SOLDERABILITY TO MIL-STD-202, M208 - REFLOW ALLOWED, IF REQUIRED

2. SCREW SIZE 4

3. DIMENSIONS APPLY PRIOR TO PLATING.

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS
DRAWING IS THE SOLE PROPERTY OF
SEASTROM MANUFACTURING. ANY
REPRODUCTION IN PART OR AS A WHOLE
WITHOUT THE WRITTEN PERMISSION OF
SEASTROM MANUFACTURING IS
PROHIBITED.

	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/32 ANGULAR: MACH ± 1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005 MATERIAL BRASS		NAME	DATE	SEASTROM MFG		
		DRAWN					
		CHECKED			SOLDER LUG		
		ENG APPR.					
		MFG APPR.					
İ		Q.A.					
		COMMENTS:			1		
- 1	FINISH					T	
	SEE NOTE 1					DWG. NO.	REV.
	DRAWING IS NOT TO SCALE				Α	5442-5-TL2	-
						SHEET 1 (OF 1