



# NOTES

- PASSIVATE PER AMS2700 METHOD 1 TYPE 2 CLASS 1
- HEAT TREAT: TH1050 CONDITION (38-44 HRC)
- DIMENSIONS APPLY BEFORE PLATING

## PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES  
TOLERANCES:  
FRACTIONAL  $\pm 1/32$   
ANGULAR: MACH  $\pm 1/2$  Deg  
TWO PLACE DECIMAL  $\pm .01$   
THREE PLACE DECIMAL  $\pm .005$

MATERIAL  
17-7PH STAINLESS STEEL

FINISH  
SEE NOTE 1

DRAWING IS NOT TO SCALE

	NAME	DATE	SEASTROM MFG	
DRAWN				
CHECKED			CRESCENT SPRING WASHER	
ENG APPR.				
MFG APPR.				
Q.A.				
COMMENTS:			SIZE A DWG. NO. 5804-187-3-P REV. -	
			SHEET 1 OF 1	