

NOTES

1. BLACK OXIDE PER MIL-DTL-13924 CLASS 3, LIGHT OIL, NO TEST REQUIRED; w/BAKE

2. HEAT TREAT: TH1050 CONDITION (38-44 HRC)

3. NUMBER OF WAVES: 3

4. DIMENSIONS APPLY BEFORE PLATING

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SEASTROM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SEASTROM MANUFACTURING IS PROHIBITED.

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL±1/32 ANGULAR: MACH±1/2 Deg TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005	DRAWN	NAME	DATE	SEASTROM MFG		
	CHECKED			WAVE SPRING WASHER		
	ENG APPR.					
	MFG APPR.					K
17-7PH STAINLESS STEEL	Q.A.					
	COMMENTS:					
SEE NOTE 1					DWG. NO.	REV.
DRAWING IS NOT TO SCALE				Α	5806-6-3-BO	-
					ISHEET 1	OF 1